



LEDI® NETWORK ITS V2m - 2U 1 PTP output

High Accuracy secure time Server
with triple synchronization redundant inputs
and with multiple synchronization outputs

Internal Time Base

Its internal battery and its oscillator allow to provide stable time code output in case of synchronization or power supply failure.

Three quartz oscillators at choice:

	OCXO LN	OCXO	TCXO
frequency stability	5.10 ⁻¹⁰ (-10°C à 60°C)	1.10 ⁻⁹ (-20°C à 70°C)	1.10 ⁻⁶ (0°C à 60°C)
Ageing	3.10 ⁻¹⁰ / day	5.10 ⁻¹⁰ / day	2.10 ⁻⁹ / day


Security and network protocols

- **Basic power reserve included by default.** Possibility of extending the duration. *Duration varies depending on the options chosen, contact us for more details.*
- **Backup of configuration** setting in flash memory
- **Supervision** via SNMP V3 or supervision software GT SCADA or Syslog
- **Remote configuration** via secured web page
- **Configuration setting** command prompt via SSH
- **Firmware update** via FTP or SCP
- **Compatible IP v4/v6** (compatible DHCP v4/v6)
- **Configuration on Web interface via HTTP et HTTP(s)**
- **Secure access** to web interface by identifier and password
- **Authentication protocol and MD5 encryption**
- **Network communication** ports can be disabled
- **PTPv2 IEEE 1588** (TELECOM, ENERGIE... profiles)

Specifications

Power supply	110-250VAC – 1,4 A max. – 50/60Hz – type IEC 60320 defined C14 and 18 - 36 VDC or 36 – 72 VDC – 2 points screw terminal block
Power Cable	IEC 60320 defined C13 / MALE SCHUKO 2 (EUROPE) & (Type F)*
Certifications	CE, EN62368 (safety), EN 55032 (EMC transmission), EN 55035 (EMC immunity), ROHS
Maximal Consumption	20 VA
IP	31
MTBF	110 000 h
MTBF/ MTTR	Mother board: 10 min Display board: 5 min Output board: 5 min
Weight	2,3 kg
Dimensions	19" 2U Rack. 482x88x266 mm (LxHxD)
Display	Orange OLED screen with backlight
Operating Temperature / hygrometry	-20 à 50°C / 0 à 90% HR
Storage temperature / hygrometry	-20 to 70°C / 10 to 85% HR
Maximum operating/ storage altitude	3 500 m (11 483 ft)

*For other types of power cables, refer to the power cable reference table



Key features

- 1 PTP output on RJ45 or SFP (optical fiber)
- NTP/SNTP output included by default on RJ45
- Power Supply Redundancy 18-36 or 36-72 VDC with 110-250 VAC
- Configurable priorities of synchronization inputs
- Compensation of input delay due to transmission distance and threshold setting for security
- Time Base and algorithm ensuring output accuracy up to 50ns when synchronized to GPS/GNSS
- Independence and modularity of output boards
- PPS and 10Mhz output (available with OCXO oscillator only) via BNC connectors
- Alarm management via SNMP TRAP (V1, V2C, V3) and two static relay outputs on screw terminal for synchronization and power supply alarms
- Manual or automatic adjustment for transmission delay
- Local or UTC time display on front panel

Configuration

- Remote Configuration and time setting via embedded web interface
- Automatic Time offset and DST on outputs
- IP Configuration by front panel keyboard
- Configuration file can be retrieved and uploaded via secured web interface
- Auto-IP v4

Synchronization inputs

1st time reference input (at choice):

- Multi-constellation GNSS Receiver: (GPS, GLONASS, BEIDOU, GALILEO) or GPS; Cold start, accuracy 10 to 50 ns; Cold start, précision 10 à 50 ns
- ASCII (NMEA 0183 RMC or ZDA by auto-detection) + TOP
- PPS input

2nd time reference input (at choice):

- AFNOR NFS 87-500/IRIG B/ IEEE1344
- NTP (V2, V3, V4) 10/100BaseT

3rd reference input (backup):

- Frequency input (between 1kHz and 10MHz)

Synchronization outputs

- Multiple outputs
- NTP/SNTP output included by default on RJ45
- PPS and 10Mhz output (available with OCXO oscillator only) via BNC connectors

NB: The RJ45 ports of the optional NTP outputs are independent and isolated by means of protocol break.

GNSS Antenna (option)

- For more information on our GNSS antennas, refer to the technical specifications (see reference table 92225/)

Storage Conditions

Conditions	Temperature	Hygrometry	Maximum cumulated duration
Extreme	-20°C to 0°C	10 to 85% HR	48h
Extreme	40°C to 70°C	10 to 85% HR	48h
Normal	10°C to 40°C	10 to 85% HR	6 months

The product must be lit for 4 hours every 3 months to keep its characteristics. see the user manual for more information.

